


EXTERNAL FINISH


 PROFILED STEEL PANEL WALLS


 FLAT STEEL PANEL WALLS


WINDOWS


 WINDOW - ALUMINIUM - SINGLE 4mm CLEAR GLAZED - SLIDING - BOTH PANES TO SLIDE AND LOCK - SIZE AS REFERENCE


 WINDOW - ALUMINIUM - SINGLE 4mm CLEAR GLAZED - TOP OPENING VENT - SIZE AS REFERENCE


 WINDOW - ALUMINIUM - DOUBLE GLAZED 4mm CLEAR / 6mm / 4mm CLEAR - SLIDING - BOTH PANES TO SLIDE AND LOCK - SIZE AS REFERENCE


 WINDOW - ALUMINIUM - DOUBLE GLAZED 4mm CLEAR / 6mm / 4mm CLEAR - TOP OPENING VENT - SIZE AS REFERENCE

 WINDOW - PVCu - DOUBLE GLAZED 4mm CLEAR / 20mm / 4mm CLEAR - FULLY OPENING - LOCKABLE - SIZE AS REFERENCE

 WINDOW - PVCu - DOUBLE GLAZED 4mm CLEAR / 20mm / 4mm CLEAR - TILT/TURN - LOCKABLE - SIZE AS REFERENCE

 WINDOW - PVCu - DOUBLE GLAZED 4mm CLEAR / 20mm / 4mm CLEAR - FIXED - SIZE AS REFERENCE

 WINDOW - HIGH LEVEL - ALUMINIUM - SINGLE 4mm OBSCURE GLAZED - SLIDING - ONE PANE FIXED AND ONE PANE TO SLIDE AND LOCK - SIZE AS REFERENCE

 WINDOW - HIGH LEVEL - PVCu - DOUBLE GLAZED 4mm OBSCURE / 20mm / 4mm CLEAR - FULLY OPENING - SIZE AS REFERENCE

TG TOUGHENED GLAZING

 WINDOW EXTERNAL SHUTTER - MILD STEEL

 WINDOW EXTERNAL MESH GUARD - POWDER COATED - WHITE

 TYPE + COLOUR ROLLER SHUTTER - POWDER COATED - TYPE & COLOUR AS REFERENCE

 WINDOW BLIND - VENETIAN


 WINDOW BLIND - VERTICAL


(ROLLER) WINDOW BLIND - ROLLER

((FC - RATING))) FIRE CURTAIN - FIRE RESISTANCE IN MINUTES AS REFERENCE

DOORS

 EXTERNAL PERSONNEL DOOR - MILD STEEL - NON INSULATED - SIZE & FURNITURE AS REFERENCE

 EXTERNAL PERSONNEL DOOR - MILD STEEL - INSULATED SPECIFICATION - SUPERGLASS MAT 40 - SIZE & FURNITURE AS REFERENCE

 INTERNAL PERSONNEL DOOR - BLONDE OAK - HOLLOW CORE UNLESS INDICATED - SIZE & FURNITURE AS REFERENCE

PVCu PVCu SPECIFICATION DOOR

ALUM ALUMINIUM SPECIFICATION DOOR

EG EXTERIOR GRADE SPECIFICATION - INTERNAL DOOR - STAIN FINISHED UNLESS INDICATED

SC SOLID CORE SPECIFICATION - INTERNAL DOOR

2XG GLAZED - TOP PANEL ONLY

2XGG GLAZED - TOP AND BOTTOM PANEL

VP - GWPP VISION PANEL - GEORGIAN WIRED POLISHED PLATE GLASS

VP - TG VISION PANEL - TOUGHENED GLASS

DLS DEADLOCK - 5 LEVER

AP PADLOCK - ARMoured

BB1 BARREL BOLT - STRIAIGHT

BB2 BARREL BOLT - SWAN NECK

SB1 SPRING BOLT - 16mm DIAMETER x 265mm

SB2 SPRING BOLT - 12mm DIAMETER x 160mm

SB3 SPRING BOLT - 10mm DIAMETER x 144mm

ML MORTICE LOCK

RML REBATED MORTICE LOCK

FE FIRE EXIT

EO EXTERNAL OVERRIDE - FITTED TO FIRE EXIT

FL/TL FACILITY LEVER & TUBULAR LATCH - FITTED TO DISABLED WC DOOR

BL BATHROOM LOCK

IB1 INDICATOR BOLT

IB2 INDICATOR BOLT C/W EXTERNAL RELEASE

IB3 INDICATOR BOLT - OUTWARD OPENING

DC1 DOOR CLOSER - EXTERNAL

DC2 DOOR CLOSER - INTERNAL

WTT WEATHER THRESHOLD TRIM

DGL1 DIGITAL CODE MORTICE LOCK - EXTERNAL

DGL2 DIGITAL CODE MORTICE LOCK - INTERNAL DOOR

DGL3 DIGITAL CODE MORTICE LOCK - INTERNAL HALF GLAZED DOOR


CH CABIN HOOK


((FC - RATING))) FIRE CURTAIN - FIRE RESISTANCE IN MINUTES AS REFERENCE

EXTERNAL FITTINGS

 PROTECTIVE SHROUD - FOR SERVICE CONNECTIONS

 PROTECTIVE SHROUD - REMOVABLE FOR SERVICE CONNECTIONS

 CLOSE COUPLED LINK FACILITY

 CABLE ENTRY TUBE - 25mm C/W EXTERNAL CAP (SHOWN WITHIN EXTERNAL WALL)

 LOUVRE VENT - EXTERNAL - SIZE AS REFERENCE

VENT H VENT - HIGH LEVEL

VENT L VENT - LOW LEVEL

VENT R VENT - ROOF LEVEL

LB L LADDER BRACKET

CG C CABLE GUIDES

 RWP RAIN WATER PIPE & GUTTERING

CS1 CLIENT STICKER

CS2 CLIENT SIGN

SP SIGN PLATE - ALUMINIUM - POSITION & SIZE AS PER STICKER DRAWING

GENERATORS

GVO GENERATOR VENT OUT

GVI GENERATOR VENT IN

GCP GENERATOR CONTROL PANEL

GFF GENERATOR FUEL FILLER

GE GENERATOR EXHAUST

GEM GENERATOR ENGINE MANAGEMENT

DRAWING LEGEND

Issue	Page
36	1 OF 4



ELECTRICAL - LIGHTING

- WALL LIGHT SWITCH - 1 GANG/1 WAY
- WALL LIGHT SWITCH - 2 GANG/1 WAY
- WALL LIGHT SWITCH - 1 GANG/2 WAY
- DIMMER LIGHT SWITCH
- OVERRIDE SWITCH FOR MOTION SENSOR - OFF ONLY
- PULL LIGHT SWITCH
- OVERRIDE PULL SWITCH FOR MOTION SENSOR - OFF ONLY
- KEY SWITCH FOR EMERGENCY LIGHT
- ROCKER SWITCH FOR ELECTRIC ROLLER SHUTTER
- BULKHEAD LIGHT - EXTERNAL
- BULKHEAD LIGHT - EXTERNAL C/W P.I.R
- FLOOD LIGHT - EXTERNAL
- BULKHEAD LIGHT - SLIM-LINE - EXTERNAL DUSK TO DAWN / ENERGY SAVING
- BULKHEAD LIGHT - SLIM-LINE - EXTERNAL C/W P.I.R
- FLOOD LIGHT - EXTERNAL C/W P.I.R
- BULKHEAD LIGHT - EXTERNAL C/W P.I.R / HIGH FREQUENCY 3 HOUR EMERGENCY
- BULKHEAD LIGHT - INTERNAL
- EMERGENCY LIGHT - 3 HOUR NON-MAINTAINED
- EMERGENCY LIGHT - 3 HOUR MAINTAINED
- FLUORESCENT LIGHT - SINGLE T8 TUBE - SIZE AS REFERENCE
- FLUORESCENT LIGHT - TWIN T8 TUBE - SIZE AS REFERENCE
- READING LIGHT C/W PULLSTRING
- 360° CEILING MOUNTED MOTION SENSOR
- 120° WALL MOUNTED MOTION SENSOR
- CAT2 CAT2 SPECIFICATION LIGHT FITTING
- HF HIGH FREQUENCY SPECIFICATION LIGHT FITTING
- T5 T5 SPECIFICATION LIGHT FITTING
- DIFF DIFFUSER
- VP VAPOUR PROOF SPECIFICATION LIGHT FITTING
- DIM DIMMABLE SPECIFICATION LIGHT FITTING
- MESH REINFORCED MESH SPECIFICATION LIGHT FITTING

ELECTRICAL - CIRCUIT PROTECTION & CONTROL

- MAINS BOARD - SINGLE PHASE
- MAINS BOARD - THREE PHASE
- 7 DAY TIMER - FITTED IN MAINS BOARD
- EARTH BOLT
- ANGLED APPLIANCE INLET - SIZE AS REFERENCE
- STRAIGHT CONNECTOR TO SUIT INLET - SIZE AS REFERENCE SUPPLIED LOOSE
- EXTERNAL SOCKET OUTLET - SIZE AS REFERENCE
- EXTERNAL SOCKET OUTLET C/W SWITCH - SIZE AS REFERENCE
- EXTERNAL ROTARY SURFACE ISOLATOR - SIZE AS REFERENCE
- ELECTRICAL ENERGY MONITOR
- WEATHER RESISTANT IP55 JUNCTION BOX - SURFACE MOUNTED PLASTIC ENCLOSURE
- WEATHER RESISTANT IP56 JUNCTION BOX - SURFACE MOUNTED PLASTIC ENCLOSURE

ELECTRICAL - WIRING DEVICES

- DOUBLE SOCKET - HIGH LEVEL
- DOUBLE SOCKET - WITHIN TRUNKING
- DOUBLE SOCKET - LOW LEVEL
- SINGLE SOCKET - HIGH LEVEL
- SINGLE SOCKET - WITHIN TRUNKING
- SINGLE SOCKET - LOW LEVEL
- FUSED SPUR - SWITCHED
- FUSED SPUR - UNSWITCHED
- EARTH BOND - SPARE
- TELEPHONE POINT
- THERMOSTAT - STANDARD
- THERMOSTAT - TAMPER PROOF
- COOKER POINT
- SHAVER SOCKET
- IP-RATED WEATHER RESISTANT - RATING AS REFERENCE
- FM FLOOR MOUNTED
- CM CEILING MOUNTED

ELECTRICAL - HEATING & VENTILATION

- EXTRACTION FAN - WALL MOUNTED - SIZE AS REFERENCE
- EXTRACTION FAN C/W HUMIDISTAT - WALL MOUNTED - SIZE AS REFERENCE
- EXTRACTION FAN - CEILING MOUNTED - SIZE AS REFERENCE
- HAND DRYER 1.8KW - WARNER HOWARD
- HAND DRYER 2.4KW - NEWLEC
- HAND DRYER - MITSUBISHI JET
- HAND DRYER 2.5KW - WARNER HOWARD
- HAND DRYER - 1.1KW - WARNER HOWARD AIRFORCE
- AIR CONDITIONING - INTERNAL UNIT - COOLING CAPACITY AS REFERENCE/HEATING CAPACITY AS REFERENCE - MOUNTED ON INTERNAL WALL ABOVE WINDOW HEIGHT
- AIR CONDITIONING - EXTERNAL CONDENSER UNIT - MOUNTED ON CANTILEVER BRACKETS ON EXTERNAL WALL BELOW WINDOW HEIGHT - UNIT IS FITTED WITH AN EXTERNAL DRAINAGE PIPE DISCHARGING TO GROUND
- CONVECTOR HEATER C/W THERMOSTAT - SIZE AS REFERENCE
- PANEL HEATER C/W THERMOSTAT - SIZE AS REFERENCE
- FAN HEATER C/W THERMOSTAT - SIZE AS REFERENCE
- COLDWATCHER HEATER - SIZE AS REFERENCE
- TUBULAR HEATER & GUARD - SIZE AS REFERENCE
- OIL FILLED RADIATOR C/W THERMOSTAT - SIZE AS REFERENCE
- (T) 24 HOUR TIMER SPECIFICATION HEATER
- MESH MESH GUARD FITTED TO HEATER
- Def DEFLECTOR SPECIFICATION CONVECTOR HEATER

ELECTRICAL - COMMUNICATIONS & DATA CABLING

- 16 PORT SWITCH 10/100 MBPS C/W PATCH LEADS
- RJ45 2-WAY DATA SOCKET - WIRED USING CAT 5E CABLE TO T568B
- RJ45 4-WAY DATA SOCKET - WIRED USING CAT 5E CABLE TO T568B
- VOICE CONVERTER - FITTED TO SINGLE RJ45 DATA SOCKET
- HDMI SOCKET
- TYPE TRUNKING - TYPE AS REFERENCE
- NW WIRING NOT INCLUDED

DRAWING LEGEND

Issue	Page
3.6	2 OF 4



ELECTRICAL - ALARMS + ACCESS CONTROL

- ALARM - DISABLED WC - SOUNDER & LIGHT
- ALARM - DISABLED WC - PULL CORD
- ALARM - DISABLED WC - MASTER RESET
- SMOKE ALARM - MAINS WITH BATTERY BACKUP - IONISATION
- SMOKE ALARM - BATTERY
- SMOKE DETECTOR & SOUNDER - FIRE ALARM
- SMOKE DETECTOR - FIRE ALARM
- HEAT DETECTOR - FIRE ALARM
- HEAT DETECTOR C/W SOUNDER - FIRE ALARM
- HEAT ALARM - MAINS WITH BATTERY BACKUP
- INTERNAL SOUNDER
- MANUAL CALL POINT
- PASSIVE INFRA RED DETECTOR
- EXTERNAL BELLBOX & STROBE
- DOOR CONTACT
- TELEPHONE TO RELEASE BUTTON
- PUSH TO RELEASE BUTTON
- MAGNETIC DOOR RELEASE
- FIRE ALARM MAIN PANEL
- INTRUDER ALARM MAIN PANEL
- INTRUDER ALARM REMOTE KEYPAD
- ACCESS CONTROL MAIN PANEL
- ACCESS CONTROL KEYPAD WITH CAMERA
- ALARM - EXTERNAL SOUNDER

ELECTRICAL - WATER HEATING

- WATER HEATER - STORAGE 2KW OVERSINK 5L
- WATER HEATER - INSTANTANEOUS 3KW OVERSINK - TOUCH FREE
- WATER HEATER - STORAGE 2KW UNDERSINK 10L
- WATER HEATER - STORAGE 3KW 25L GRAVITY FED - POSITIONED AT HIGH LEVEL
- WATER HEATER - STORAGE 3KW 10L - POSITIONED AT HIGH LEVEL
- WATER HEATER - STORAGE 2KW UNDERSINK 15L
- WATER HEATER - STORAGE 3KW UNDERSINK 15L
- WATER HEATER - STORAGE 2KW UNDERSINK 5L
- WATER HEATER - STORAGE 3KW UNDERSINK 10L
- WATER HEATER - STORAGE 3KW 30L - POSITIONED AT HIGH LEVEL
- WATER HEATER - STORAGE 3KW 50L - POSITIONED AT HIGH LEVEL
- WATER HEATER - STORAGE 3KW 100L - POSITIONED AT HIGH LEVEL
- ZIP INSTANT BOILING WATER SYSTEM - 15KW, 3 LITRE, 18 CUP
- ZIP INSTANT BOILING WATER SYSTEM - 2.4KW, 5 LITRE, 30 CUP
- ZIP INSTANT BOILING WATER SYSTEM - 2.4KW, 7.5 LITRE, 45 CUP
- INLINE FILTER FITTED TO ZIP INSTANT BOILING WATER SYSTEM
- DRIP TRAY FOR ZIP INSTANT BOILING WATER SYSTEM
- ELECTRIC SHOWER HEATER - SIZE AS REFERENCE

FURNITURE & INTERNAL FITTINGS - LOCKERS

- SOLID LOCKER - NUMBER OF COMPARTMENTS AS REFERENCE - 300mm (D) x 300mm (W) x 1800mm (H) - NO FEET - POWDER COATED FINISH IN LIGHT GREY UNLESS OTHERWISE SPECIFIED
- MESH LOCKER - NUMBER OF COMPARTMENTS AS REFERENCE - 300mm (D) x 300mm (W) x 1980mm (H) - INCLUDING 150mm FEET - GALVANISED FINISH
- L1 DEAD LOCK C/W 2 KEYS
- L2 HASP & STAPLE - NO PADLOCK
- L3 HASP & STAPLE - C/W PADLOCK

FURNITURE & INTERNAL FITTINGS - FITTINGS

- NB1 NOTICE BOARD - 1200mm (W) X 1200mm (H) - SUNDEALA 9mm - PLASTIC TRIM
- NB2 NOTICE BOARD - 2400mm (W) X 1200mm (H) - SUNDEALA 9mm - PLASTIC TRIM
- NB3 NOTICE BOARD - 1800mm (W) X 1200mm (H) - SUNDEALA 9mm - PLASTIC TRIM
- NB4 BLUE BOARD - 1800mm (W) X 1200mm (H) - BLUE FELT - ALUMINIUM TRIM
- NB5 NOTICE BOARD - 1600mm (W) X 1200mm (H) - SUNDEALA 9mm - PLASTIC TRIM
- NB6 NOTICE BOARD - 2000mm (W) X 1200mm (H) - SUNDEALA 9mm - PLASTIC TRIM
- WB1 WHITE BOARD - 1200mm (W) X 900mm (H)
- WB2 WHITE BOARD - 1800mm (W) X 900mm (H)
- WT WORKTOP
- FB FIRE BLANKET
- HAT & COAT HOOKS - QUANTITY AS SHOWN
- TOILET ROLL HOLDER - SUPPLIED WITHOUT TOILET ROLL
- MIRROR - 300mm (W) X 450mm (H)
- DUCK BOARD - 500mm (W) X 383mm (L)
- PAPER TOWEL DISPENSER - SUPPLIED WITHOUT PAPER TOWELS
- DEB NATURALLY SKIN SAFETY CENTRE - 800mm (W) X 570mm (H) - 1 X PROTECT (1000ml), 1 X CLEANSE LIGHT (2000ml), 1 X CLEANSE HEAVY (4000ML), 1 X RESTORE (1000ml)
- DEB NATURALLY MINI SKIN SAFETY CENTRE - 590mm (W) X 510mm (H) - 1 X PROTECT (1000ml), 1 X CLEANSE (2000ml), 1 X RESTORE (1000ml)
- DEB CRADLE SKIN SAFETY CENTRE - 350mm (W) X 335mm (H) - 1 X PROTECT (700ml), 1 X CLEANSE (750ml), 1 X SANITISER (700ml)
- VANTY PANEL
- SSB SPLASHBACK - STAINLESS STEEL
- PSB SPLASHBACK - PVCu
- SOAP DISPENSER - SUPPLIED WITHOUT SOAP

FLOOR

- CARPET TILES
- STEEL DURBAR FLOORING
- MATWELL - COCONUT

DRAWING LEGEND	
Issue	Page
3.6	3 OF 4



FURNITURE & INTERNAL FITTINGS - TABLES & SEATING




TABLE & SLATTED BENCH SEATING - SIZE AS REFERENCE





TABLE & POLYPROPYLENE SEATING - SEAT COLOUR AS REFERENCE



BENCH SEATING - SLATTED TIMBER - STAINED FINISH



CHAIR - POLYPROPYLENE STACKING




CHAIR - HIGH BACK OFFICE



CHAIR - UPHOLSTERED STACKING

FURNITURE & INTERNAL FITTINGS - STORAGE



BASE UNIT - WHITE UNLESS SPECIFIED - SIZE AS REFERENCE



WALL UNIT - WHITE UNLESS SPECIFIED - SIZE AS REFERENCE



STEEL RACKING - TIER AS REFERENCE

PLUMBING - SERVICES

- WATER METER
- AIR ADMITTANCE VALVE
- COLD WATER FEED CONNECTION FOR DISHWASHER, WASHING MACHINE OR SIMILAR
- WASTE OUTLET FOR DISHWASHER, WASHING MACHINE OR SIMILAR
- 15mm MAINS WATER INLET
- 22mm MAINS WATER INLET
- 40mm WASTE OUTLET
- 110mm WASTE OUTLET

PLUMBING - BASINS & SINKS



WASH HAND BASIN - VITREOUS CHINA - HSE COMPLIANT SIZE - COLD BASIN PILLAR TAP ONLY



WASH HAND BASIN - VITREOUS CHINA - HSE COMPLIANT SIZE - HOT & COLD BASIN PILLAR TAPS



WASH HAND BASIN - VITREOUS CHINA - COMPACT SIZE - COLD BASIN PILLAR TAP ONLY



WASH HAND BASIN - VITREOUS CHINA - COMPACT SIZE - HOT & COLD BASIN PILLAR TAPS



WASH HAND BASIN - POLYETHYLENE - GREY - HSE COMPLIANT SIZE & COLD TAP ONLY - WATER TANK CAPACITY 60 LITRES - REQUIRING INTERNAL FILLING UNLESS OTHERWISE SPECIFIED - WASTE DISCHARGES INTO COMPANION WC TANK WHERE FITTED



SINK - VITREOUS CHINA - BELFAST SIZE - COLD BIB TAP ONLY



SINK - VITREOUS CHINA - BELFAST SIZE - HOT & COLD BIB TAPS



SINK - STAINLESS STEEL - COLD HIGH NECK PILLAR TAP ONLY




SINK - STAINLESS STEEL - HOT & COLD HIGH NECK PILLAR TAPS




SINK - STAINLESS STEEL - INSET - COLD HIGH NECK PILLAR TAP ONLY



SINK - STAINLESS STEEL - INSET - HOT & COLD HIGH NECK PILLAR TAPS



WASH TROUGH - STAINLESS STEEL - SIZE AS REFERENCE - COLD BASIN PILLAR TAP ONLY



WASH TROUGH - STAINLESS STEEL - SIZE AS REFERENCE - HOT & COLD BASIN PILLAR TAPS

NC1 TAP - NON-CONCUSSIVE - COLD TAP ONLY

NC2 TAP - NON-CONCUSSIVE - HOT & COLD TAP

BT1 TAP - BIB, EXTERNAL

BT2 TAP - BIB, INTERNAL

LT TAP - LEVER

MT TAP - MIXER


PLUMBING - SHOWERS



SHOWER TRAY - CREAM - 745mm (W) x 684mm (L) + WALL LINER - CREAM C/W CURTAIN - WHITE



SHOWER TRAY - WHITE - SIZE AS REFERENCE + CUBICLE ENCLOSURE C/W DOOR - DOOR TYPE AS REFERENCE



SHOWER TRAY - WHITE - 1200mm (W) X 750mm (L) - LOW LEVEL DISABLED C/W WALL LINER - WHITE - FOLDING DOORS + FOLDING SEAT + CURTAIN - WHITE

PLUMBING - TOILETS & URINALS



WC PAN - VITREOUS CHINA - WHITE, CISTERN 6 LITRES & TOILET SEAT



WC PAN - VITREOUS CHINA - WHITE - DISABLED LOW LEVEL, CISTERN 6 LITRES, TOILET SEAT & GRAB RAILS




GRAB RAIL - DISABLED



DF DUAL FLUSH FACILITY ON WC - PART FLUSH IS 4 LITRES / FULL FLUSH IS 6 LITRES



MAC MACERATOR FITTED TO WC



WC - POLYETHYLENE - GREY - RE-CIRCULATING TANK, CAPACITY 225 LITRES - REQUIRES INTERNAL EMPTYING



URINAL - VITREOUS CHINA



URINAL - VITREOUS CHINA - TIMED FLOW VALVE



URINAL - VITREOUS CHINA - WATERLESS



URINAL TROUGH - STAINLESS STEEL - SIZE AS REFERENCE



C1 CISTERN 9 LITRES - URINAL



C2 CISTERN 13.5 LITRES - URINAL

PLUMBING - PUMPS, DRAINS, VALVES & ANCILLARIES



WS WATER SOFTENER



PUMP WATER PUMP



WATER PUMP C/W ENCLOSURE - ALUMINIUM - POWDER COATED - WHITE



FLOOR DRAIN



PRV PRESSURE REDUCING VALVE

PLUMBING - TANKS



WATER TANK, REQUIRING INTERNAL FILLING UNLESS NOTED, CAPACITY AS REFERENCE, NO ENCLOSURE



WASTE TANK, REQUIRING INTERNAL EMPTYING CAPACITY AS REFERENCE, NO ENCLOSURE

DRAWING LEGEND

Issue	Page
3.6	4 OF 4